

Ultraclean CTA Technical Data Sheet

Description:

Ultraclean CTA is an acidic detergent for metal descaling and brightening in ultrasonic baths.

- To be diluted with water
- General purpose cleaning
- Metal descaling and brightening
- Fair compatibility with aluminium

Applications

Used in a wide range of applications for cleaning, descaling and brightening of different components in manufacturing and processing industries. Ultraclean CTA can be used on aluminium and other soft metals.

Directions for Use

Add 20-50g of Ultraclean CTA per 1 Litre of water in the ultrasonic cleaner. Do not mix with other solutions.

The required dosage will depend on your cleaning application and the level of contamination. Items should be rinsed with water and dried immediately after processing.

Technical Data

These figures are typical and should not be interpreted as specifications, refer to MSDS for details.

Characteristic	Value/Description
Appearance	White crystalline powder
Odour	Odourless
pH (@ 1%)	1.8 @ 5% aqueous solution
Relative Density at 20°C	1.665

Available in:

- 5KG Tub (Part no. F5003501)
- 20KG Tub (Part no. F5003401)

Disposal

When diluted to concentration of 5% or less, Ultraclean CTA is not hazardous to aquatic organisms and may be safely disposed of down the drain. Refer to regional or national regulations.

Storage

36 months when stored in a cool, dark environment.