

IND145

148Litre Ultrasonic Cleaner

Ultrawave's Westeries ultrasonic cleaners are robust and reliable, delivering effective cleaning results for all manufacturing, processing and maintenance applications.



Effective cleaning and high productivity

Available from 32 to 160 Litre in capacity, multiple parts can be processed in one cycle. The improved cleaning results reduce the need for re-cleans or rejects, whilst the simple one-button-press operation allows the operator to process other tasks during the cleaning cycle.

Aqueous Cleaning

Using aqueous solutions, the IND-Series cleans with minimal environmental impact or health and safety requirements.

The stainless steel lid acts as an insulator, minimising evaporation thus lowering heating requirements, water and detergent usage.

Robust and reliable

Built with a heavy duty 316 stainless steel tank, the longevity of the IND-Series is maximised. The stainless steel basket shelf further minimises wear whilst parts are positioned to ensure maximum exposure to ultrasonic cleaning activity. The warranty is supported by Ultrawave's dedicated After Sales Department.

Standard features

- 316 industrial grade stainless steel tank
- Digital control for time and temperature
- Fluid level protection
- Safety thermal cut off

Specifications are subject to change for continual improvements

- Stainless steel lockable drain valve
- Stainless steel lid and basket
 - Basket shelf





Warranty

Ultrawave Ltd Eastgate Business Park, Wentloog Avenue Cardiff CF3 2EY, United Kingdom +44 (0) 845 330 4236 www.ultrawave.co.uk

IND145

148Litre Ultrasonic Cleaner

Construction Case	304 Stainless Steel
Construction Tank	316 Stainless Steel (2mm)
Control	Digital (Time and Temperature)
Overall Dimensions	765 x 710 x 695mm (WxDxH)
Internal Tank Dimensions	600 x 450 x 550mm (WxDxH)
Basket Dimensions	570 x 420 x 485mm (WxDxH)
Tank Capacity	148 Litres
Working Capacity	131 Litres
Basket Capacity	116 Litres
Ultrasonic Power	1200W
Ultrasonic Power (per litre)	9/Litre
Operating Frequency	30 - 40KHz
Maximum Heating Capacity	Ambient - 80°C
maximan nearing capacity	
Heater Power	2kW
	2kW 0 – 99 minutes
Heater Power	
Heater Power Timer	0 – 99 minutes
Heater Power Timer Mains Connection	0 – 99 minutes 230Vac, 50Hz, 13A plug
Heater Power Timer Mains Connection Drain Outlet	0 – 99 minutes 230Vac, 50Hz, 13A plug ¾" BSP Stainless Steel
Heater Power Timer Mains Connection Drain Outlet Lid	0 – 99 minutes 230Vac, 50Hz, 13A plug ¾" BSP Stainless Steel 304 Stainless Steel
Heater Power Timer Mains Connection Drain Outlet Lid Basket Optional lockable wheeled stand	0 – 99 minutes 230Vac, 50Hz, 13A plug ¾" BSP Stainless Steel 304 Stainless Steel 304 Stainless Steel 304 Stainless Steel

1 year standard Options available for 3Year or 5year extended warranty as part of the Planned Preventative Maintenance Service

as part of the Planned Preventative Maintenance Service (PPMS)

